



😊😐😞 **MUHAMMAD FAISAL** 😊😐😞

**MIT 4<sup>th</sup> Semester**

**Al-Barq Campus (VGJW01) Gujranwala**

**[faisalgrw123@gmail.com](mailto:faisalgrw123@gmail.com)**

**CS411 Mega OBJECTIVE File for Final Term Papers**

**CS411 – VISUAL PROGRAMMING**

**Question No: 1 (Marks: 1) - Please choose one**

A\An \_\_\_\_\_ displays the map and the labels for the recorded locations.

- **mkMapView** (Page#213)
- uiactivityindicatorview
- uitextfield
- mapmkview

**Question No: 2 (Marks: 1) - Please choose one**

\_\_\_\_\_ properties based on input or mouse clicks.

- HTML
- **CSS** (Page#180)
- C#
- XML

**Question No: 3 (Marks: 1) - Please choose one**

---

Which of the following "Event" property is used to show the "distance (in pixels)" of the mouse pointer from left edge of the Monitor?

- pageX
- pageY
- ScreenY
- **ScreenX** (Page#205)

**Question No: 4 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ was introduced in 95 by netscape.

- C ++
- . Net
- **Javascript** (Page#179)
- PHP

**Question No: 5 (Marks: 1) - Please choose one**

---

Web servers receive request and responds as \_\_\_\_\_.

- Html only
- Plain Text only
- JSON only
- **Html, plain text and JSON** (Page#211)

**Question No: 6 (Marks: 1) - Please choose one**

---

Concurrent collections may not useful when you want a thread-safe collection three static methods in the Parallel class.

True

**False** (Page#175)

**Question No: 7 (Marks: 1) - Please choose one**

---

We can return a \_\_\_\_\_ from void function without explicitly return it.

- value
- event
- **task** (Page#169)
- function

**Question No: 8 (Marks: 1) - Please choose one**

---

The pairing of labels and arguments is an important feature of \_\_\_\_\_.

- C++
- Scripts
- **Objective-C** (Page#217)
- PHP

**Question No: 9 (Marks: 1) - Please choose one**

---

Thread pool save time of thread \_\_\_\_\_.

- insertion
- **creation** (Page#160)
- deletion
- updation

**Question No: 10 (Marks: 1) - Please choose one**

---

What is NSMutableArray?

- Object
- **Class Reference** (Page#217)
- Method
- Group

**Question No: 11 (Marks: 1) - Please choose one**

---

In the \_\_\_\_\_, the target is updated whenever the source changes.

- Binding Object
- **Binding Mode** (Page#153)
- Data Mode
- Data Object

**Question No: 12 (Marks: 1) - Please choose one**

---

Which of the following "Event" property is used to show the "distance (in pixels)" of the mouse pointer from top edge of the Monitor?

- **ScreenY** (Page#205)
- pageX
- pageY
- ScreenX

**Question No: 13 (Marks: 1) - Please choose one**

---

Without binding you could not insert custom logic.

True

**False** (Page#153)

**Question No: 14 (Marks: 1) - Please choose one**

---

What is "nil" like?

- **Null** (Page#217)
- zero
- terminate
- move to new line

**Question No: 15 (Marks: 1) - Please choose one**

---

Sorting is applied \_\_\_\_\_ grouping.

- at initial stage
- anytime
- **before (Page#150)**
- after

**Question No: 16 (Marks: 1) - Please choose one**

---

Which of the following "Event" property is used to show the "distance (in pixels)" of the mouse pointer from top edge of the browser window?

- **pageY (Page#205)**
- pageX
- screenX
- screenY

**Question No: 17 (Marks: 1) - Please choose one**

---

Prop. Paths in Bindings are useful for master/detail interfaces.

- True (Page#150)**  
False

**Question No: 18 (Marks: 1) - Please choose one**

---

Objective-C introduces \_\_\_\_\_ messaging in C.

- **Smalltalk style (Page#217)**
- Short sessions
- Group
- New style

**Question No: 19 (Marks: 1) - Please choose one**

---

Template can be shared as \_\_\_\_\_.

- 1) data items
- 2) events
- 3) **resources** (Page#144)
- 4) files

**Question No: 20 (Marks: 1) - Please choose one**

---

Objective – c introduces \_\_\_\_\_ messaging in c?

- 1) **Smalltalk style** (Page#217)
- 2) Short session
- 3) Group
- 4) New Style

**Question No: 21 (Marks: 1) - Please choose one**

---

Navigation means managing the \_\_\_\_\_ item.

- 1) initial
- 2) last
- 3) **current** (Page#150)
- 4) any

**Question No: 22 (Marks: 1) - Please choose one**

---

Threadpool create and reduce real threads using hillclimbing algo to \_\_\_\_\_.

- 1) **To maximize CPU usage** (Page#174)
- 2) To reduce the cost of thread creation
- 3) To maximize memory utilization
- 4) To minimize CPU usage

**Question No: 23 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ style is a rule telling web browser how to display an element.

- ❖ HTML
- ❖ Java
- ❖ C#
- ❖ **CSS (Page#180)**

**Question No: 24 (Marks: 1) - Please choose one**

---

HTML is a \_\_\_\_\_ helper function.

- ❖ RQuery
- ❖ Browser
- ❖ **jQuery (Page#201)**
- ❖ JS

**Question No: 25 (Marks: 1) - Please choose one**

---

Today websites reach interactivity of \_\_\_\_\_ applications.

- ❖ web based
- ❖ **desktop (Page#179)**
- ❖ both of above
- ❖ none of given

**Question No: 26 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ is more than one thing happening at the same time.

- ❖ Cohesion
- ❖ Congruence
- ❖ Coherence
- ❖ **Concurrency (Page#169)**

**Question No: 27 (Marks: 1) - Please choose one**

---

Long running operations make application \_\_\_\_\_.

- implicit
- responsive
- **unresponsive (Page#160)**
- explicit

**Question No: 28 (Marks: 1) - Please choose one**

---

Which of the following "Event" properties is used with "key press event" to determine the numeric code for the key that was pressed? .

- Page X
- **Which (Page#205)**
- Shift Key
- Target

**Question No: 29 (Marks: 1) - Please choose one**

---

Thread-safe collection guaranteed the thread safe code.

True

**False (Page#177)**

**Question No: 30 (Marks: 1) - Please choose one**

---

MS introduced jscript. Their version of JS for IE.

**True (Page#179)**

False



**Question No: 31 (Marks: 1) - Please choose one**

---

Jquery solves \_\_\_\_\_ complexity and browser incompatibilities.

- i. . Net
- ii. C
- iii. **JS (Page#179)**
- iv. C#

**Question No: 32 (Marks: 1) - Please choose one**

---

Difference between Break and Stop is that Break reaches at least the sequential point.

- True (Page#175)**  
False

**Question No: 33 (Marks: 1) - Please choose one**

---

Sorting criteria should be same as grouping otherwise output make sense.

- True  
**False (Page#150)**

**Question No: 34 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ is more than one thing happening at the same time.

- i. Cohesion
- ii. Congruence
- iii. Coherence
- iv. **Concurrency (Page#169)**

**Question No: 35 (Marks: 1) - Please choose one**

---

A\An \_\_\_\_\_ indicates that the device is working and not stalled.

- mkMapView
- uiactivityindicatorview** (Page#213)
- UITextField
- mapView

**Question No: 36 (Marks: 1) - Please choose one**

---

We can join and use shared data.

**True** (Page#161)

False

**Question No: 37 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ solves "JavaScript" complexity and browser incompatibilities.

- Jhtml
- RQuery
- JQuery** (Page#195)
- J#

**Question No: 38 (Marks: 1) - Please choose one**

---

Template can even be auto-applied to some type by setting its datatype prop.

**True** (Page#144)

False

**Question No: 39 (Marks: 1) - Please choose one**

---

We use \_\_\_\_\_ to avoid compiler errors.

- Ⓐ data
- Ⓑ **xdata (Page#150)**
- Ⓒ ydata
- Ⓓ none of the given

**Question No: 40 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ Can add/remove/change “CSS” properties based on input or mouse clicks.

- Ⓐ J#
- Ⓑ JQuery
- Ⓒ HTML
- Ⓓ **None of the given option (Page#196)**

**Question No: 41 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ is typing together arbitrary objects.

- Ⓐ data frame
- Ⓑ data store
- Ⓒ **data binding (Page#140)**
- Ⓓ markup extension

**Question No: 42 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ Mode of binding is opposite to OneWay mode of binding.

- Ⓐ **OneWay To source (Page#165)**
- Ⓑ TwoWay
- Ⓒ One Time
- Ⓓ Two Time

**Question No: 43 (Marks: 1) - Please choose one**

---

Collection view source can be used to create \_\_\_\_\_ views and applied to targets.

- \* various
- \* old
- \* **new** (Page#150)
- \* initial

**Question No: 44 (Marks: 1) - Please choose one**

---

Which of the following "Event" property is used to show the "distance (in pixels)" of the mouse pointer from the left edge of the browser window?

- \* pageY
- \* **pageX** (Page#205)
- \* ScreenX
- \* ScreenY

**Question No: 45 (Marks: 1) - Please choose one**

---

When an item with no header selected, then a \_\_\_\_\_ returned.

- \* key value
- \* prime value
- \* **default value** (Page#140)
- \* numeric value

**Question No: 46 (Marks: 1) - Please choose one**

---

Which of the following is not a "jQuery" filter?

- \* Even
- \* Odd
- \* Has
- \* **Write** (Page#201)

**Question No: 47 (Marks: 1) - Please choose one**

---

Binding has a \_\_\_\_\_ prop and a \_\_\_\_\_ prop.

- source, destination
- source, target (Page#140)**
- target, destination
- none of the given

**Question No: 48 (Marks: 1) - Please choose one**

---

Which of the following Object creates a cancellation token?

- OperationCanceledtoken
- OperationCanceled
- CancellationToken
- CancellationTokenSource (Page#186)**

**Question No: 49 (Marks: 1) - Please choose one**

---

We can not bind to a collection.

- True
- False (Page#141)**

**Question No: 50 (Marks: 1) - Please choose one**

---

Threadpool is used to \_\_\_\_\_.

- To make easy the process of thread creation
- To make easy debugging process
- To save time of thread creation (Page#174)**
- To avoid complexity

**Question No: 51 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ and later merge the journal and provide a more streamlined interface.

- ♥ IE 6
- ♥ **IE 7 (Page#132)**
- ♥ IE 8
- ♥ IE 9

**Question No: 52 (Marks: 1) - Please choose one**

---

Methods with async are called asynchronous.

**True (Page#166)**  
False

**Question No: 53 (Marks: 1) - Please choose one**

---

Exception is raised when an item with no header selected, then a default value returned.

True  
**False (Page#140)**

**Question No: 54 (Marks: 1) - Please choose one**

---

HTML is called \_\_\_\_\_ layer.

- ♥ Physical
- ♥ Presentation
- ♥ Behavioral
- ♥ **Structural (Page#195)**

**Question No: 55 (Marks: 1) - Please choose one**

---

Data can be:

- xml file
- web service
- db table
- all of the given (Page#140)**

**Question No: 56 (Marks: 1) - Please choose one**

---

We can mix Items and item source.

True

**False (Page#142)**

**Question No: 57 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ helps apps remain oblivious to the visual tree.

- Routed Events
- Input Events (Page#116)**
- Output Events
- Obvious Events

**Question No: 58 (Marks: 1) - Please choose one**

---

Frame work element and framework content element both have a Resources prop.  
Often are style or data providers.

**True (Page#135)**

False

**Question No: 59 (Marks: 1) - Please choose one**

---

Any assembly marked with allow partially trusted callers and placed in \_\_\_\_\_ can be called by partial-trust code

- ◆ PAC
- ◆ SAC
- ◆ **GAC (Page#132)**
- ◆ RAC

**Question No: 60 (Marks: 1) - Please choose one**

---

Additional events can be used for fine grained progress.

**True (Page#133)**  
False

**Question No: 61 (Marks: 1) - Please choose one**

---

Many XBAP take advantage of navigation.

True  
**False (Page#132)**

**Question No: 62 (Marks: 1) - Please choose one**

---

Routed events are like \_\_\_\_\_ on top of .Net properties.

- ◆ Event properties
- ◆ Layer
- ◆ Properties
- ◆ **Dependency properties (Page#116)**



**Question No: 63 (Marks: 1) - Please choose one**

---

You can still use rich text and media, isolated storage up to \_\_\_\_\_, arbitrary files on host web server, use browser file open dialog for local files.

- 312kb
- 412kb
- 512kb** (Page#132)
- 1000kb

**Question No: 64 (Marks: 1) - Please choose one**

---

One of the purposes of journal is we use this in photo gallery for undoable image rotation.

- True** (Page#129)
- False

**Question No: 65 (Marks: 1) - Please choose one**

---

Use embedded resource to define a binary resource.

- True
- False** (Page#113)

**Question No: 66 (Marks: 1) - Please choose one**

---

Which of the following is Not a routing strategy?

- Tunneling
- Indirect** (Page#117)
- Bubbling
- Direct

**Question No: 67 (Marks: 1) - Please choose one**

---

Navigation can also happen between \_\_\_\_\_.

- xml files
- html files** (Page#128)
- iso files
- http files

**Question No: 68 (Marks: 1) - Please choose one**

---

The \_\_\_\_\_ statement iterates over each element in an "enumerable" object.

- Foreach** (Page#191)
- Dowhile
- While
- For

**Question No: 69 (Marks: 1) - Please choose one**

---

You can get an instance of navigation service by calling the static `navigationService.getNavigationService` method.

- True** (Page#128)
- False

**Question No: 70 (Marks: 1) - Please choose one**

---

The more the standardization on builtin commands, the more seamless and declarative the interaction can be between controls.

- True** (Page#123)
- False

**Question No: 71 (Marks: 1) - Please choose one**

---

Windows installer benefits include:

- showing custom setup UI
- arbitrary code at setup time
- register COM components and file associations
- All of the given options (Page#127)**

**Question No: 72 (Marks: 1) - Please choose one**

---

Persisting and Restoring can use registry or file system.

**True (Page#127)**

False

**Question No: 73 (Marks: 1) - Please choose one**

---

The corresponding type converter class for “Brush” class will be \_\_\_\_\_.

- BrushConverter (Page#149)**
- CastBrush
- BrushCast
- None of the given options

**Question No: 74 (Marks: 1) - Please choose one**

---

Button and textbox have direct knowledge of each other.

True

**False (Page#123)**

**Question No: 75 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ provides logic behind back and fwd.

- Hyperlink
- Journal** (Page#129)
- Container
- Navigation

**Question No: 76 (Marks: 1) - Please choose one**

---

App code-behind can not be omitted altogether.

- True
- False** (Page#125)

**Question No: 77 (Marks: 1) - Please choose one**

---

WPFS controls have built-in behavior tied to various commands.

- True** (Page#121)
- False

**Question No: 78 (Marks: 1) - Please choose one**

---

Stylus can behave like a \_\_\_\_\_ but has \_\_\_\_\_ resolution.

- Keyboard, lower
- Mouse, lower
- Mouse, higher** (Page#122)
- Keyboard, higher

**Question No: 79 (Marks: 1) - Please choose one**

---

Translation behavior has desired displacement, desired deceleration, and initial velocity.

**True (Page#117)**

False

**Question No: 80 (Marks: 1) - Please choose one**

---

Rotation behavior has desired expansion, desired deceleration, initial radius, and initial velocity.

True

**False (Page#117)**

**Question No: 81 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ defines a number of built-in commands.

OSPF

**WPF (Page#121)**

SPF

PWF

**Question No: 82 (Marks: 1) - Please choose one**

---

By convention "tunneling event" names are prefixed with \_\_\_\_\_ and just come \_\_\_\_\_ the bubbling event occurs.

View, after

View, before

**Preview, before (Page#117)**

Preview, after

**Question No: 83 (Marks: 1) - Please choose one**

---

Commands have automatic support for \_\_\_\_\_ gestures.

- input (Page#121)**
- output
- both input & output
- none of the given

**Question No: 84 (Marks: 1) - Please choose one**

---

Any number of child windows can be made by instantiating a Window derived class and calling Show.

- True (Page#124)**
- False

**Question No: 85 (Marks: 1) - Please choose one**

---

Translation behavior has desired rotation, desired deceleration, and initial velocity.

- True
- False (Page#117)**

**Question No: 86 (Marks: 1) - Please choose one**

---

All instances of routeduicommand implement icommand and support bubbling.

- True (Page#121)**
- False

**Question No: 87 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ are a more abstract and loosely coupled version of events.

- ☞ values
- ☞ **commands** (Page#121)
- ☞ functions
- ☞ numbers

**Question No: 88 (Marks: 1) - Please choose one**

---

Which "transform" property can help us to flip the element from its center?

- ScaleY
- ScaleX
- **RenderTransformOrigin** (Page#126)
- None of given options

**Question No: 89 (Marks: 1) - Please choose one**

---

Manipulation \_\_\_\_\_ starting event when all fingers loose contact even before a completed event.

- ☞ event
- ☞ container
- ☞ **inertia** (Page#117)
- ☞ function

**Question No: 90 (Marks: 1) - Please choose one**

---

Page does everything window does except:

- ☛ uploading and downloading
- ☛ **onclosed and onclosing** (Page#128)
- ☛ onclosed and navigating
- ☛ navigating and onclosing

**Question No: 91 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ behavior has desired rotation, desired deceleration, and initial velocity.

- Rotation** (Page#117)
- Translation
- Expansion
- None of the given

**Question No: 92 (Marks: 1) - Please choose one**

---

An "UIElement" receives mouse events only if "IsHitTestVisible" is \_\_\_\_\_.

- 0
- False
- Null** (Page#121)
- True

**Question No: 93 (Marks: 1) - Please choose one**

---

By default, initialvelocity and initialradius are initialized with the \_\_\_\_\_ values.

- coming
- current** (Page#117)
- multiple
- significant

**Question No: 94 (Marks: 1) - Please choose one**

---

Starting and started events \_\_\_\_\_ to customize or cancel or disallow some manipulations.

- stop
- end
- not allowed
- allow** (Page#116)



**Question No: 95 (Marks: 1) - Please choose one**

---

With navigation, content is usually in \_\_\_\_\_ a simpler version of Window.

- Frame
- Page (Page#128)**
- Box
- Button

**Question No: 96 (Marks: 1) - Please choose one**

---

Manipulations always done relative to a manipulation \_\_\_\_\_.

- event
- container (Page#117)**
- inertia
- function

**Question No: 97 (Marks: 1) - Please choose one**

---

Modal dialogs include \_\_\_\_\_ which are actually provided by win32.

- interfaces
- common dialogs (Page#126)**
- designs
- structure

**Question No: 98 (Marks: 1) - Please choose one**

---

\_\_\_\_\_ behavior has desiredexpansion, desireddeceleration, initialradius, and initialvelocity.

- Rotation
- Translation
- Expansion (Page#117)**
- None of the given

**Question No: 99 (Marks: 1) - Please choose one**

---

A Page can interact with its navigation container by using \_\_\_\_\_, which exposes relevant functionality regardless of whether the container is a navigation window or a Frame.

- navigation class
- navigation service class (Page#128)**
- navigation page class
- navigation box class

**Question No: 100 (Marks: 1) - Please choose one**

---

One \_\_\_\_\_ Thread and one render thread can create more with Dispatcher.Run which can improve responsiveness.

- EU
  - UI (Page#125)**
  - IU
  - IE
-



# CS411

## VISUAL PROGRAMMING

### Final Term Quizzes MCQ's

1) While Manipulation, we combine information from multiple \_\_\_\_\_.

functions

**events** (Page#116)

integers

numbers

2) In Xaml browser application, how much isolated memory we can use?

256kb

128

**512**

1024

3) \_\_\_\_\_ behavior has desired displacement, desired deceleration, and initial velocity.

Rotation

**Translation** (Page#117)

Expansion

None of the given

4) AJAX stands for \_\_\_\_\_.

Abstract JSON and XML

Asynchronous JavaScript and XHTML

**Asynchronous JavaScript and XML**

Abstract Java and XML Library

5) Which of the following technologies is not used in AJAX?

DOM

DHTML

**Flash**

CSS

6) To be boundary aware manipulation boundary feedback \_\_\_\_\_ is used.

**event** (Page#118)

container

inertia

function

7) Which of these are defined as the model object?

```
UILabel *questionField;  
NSMutableArray *questions@field;  
NSMutableArray *questions;  
Question= 0;
```

8) Which of the following is correct way to temporarily stop execution of a thread object named as “myThread” for 500 milisec?

```
myThread.Sleep(0.50);  
myThread.Stop(0.05);  
myThread.Sleep(500);  
myThread.Stop(500);
```

9) “async” and \_\_\_\_\_ keywords in C# are the heart of asynchronous programming.

Return  
**Await**  
Wait  
String

10) Controls have logic to \_\_\_\_\_ with commands through Command property.

design  
**interface** (Page#121)  
structure  
none of the given

**11)** Which of the following C# Method reports a progress change?

Finalize

**OnReport**

GetType

GetHashCode

**12)** Which of the followings are keyboard events?

Key entered, key exist

Key strike, key release

**Key down, key up**

Key pressed, key released

**13)** In case of HTML page navigation, you must use the \_\_\_\_\_ of "Navigate" that \_\_\_\_\_ a URI.

Overload, rejects

**Overload, accepts**

IFrame, rejects

IFrame, accepts

**14)** Which one of the following can be used to set dependency property values?

Temporary resource

Permanent resource

**Dynamic resource**

Static resource

**15)** Child window like parent window but gets closed when parent and similarly minimized, also called \_\_\_\_\_.

modeless area

**modeless dialog** (Page#124)

modeless interface

modeless design

**16)** "Binding" technique binds two properties together and keeps a \_\_\_\_\_ open.

Memory location

**Communication channel**

Selection

Choice

**17)** A/An \_\_\_\_\_ screen is an image that appears while a game or program is loading

Opening

Startup

Initial

**Splash**

**18)** If we insert some objects in a single cell in Grid panel, then these objects are placed on \_\_\_\_\_.

**One on Top of the other**

One after the other

One on Bottom of the other

One on Side of the other

**19)** In a code segment, if the Visibility="Collapsed" then which of the following events are not generated?

- Routed Events
- Keyboard Events
- Key down Events
- Mouse Events**

**20)** Which of the following operation cannot be performed by using a View?

- Sorting
- Grouping
- Searching**
- Filtering

**21)** lickonce benefits include:

- builtin support for automatic updates
- rollback to prev versions
- both of above options (Page#127)**
- none of the given

**22)** In order to resize the row and column in Grid panel, \_\_\_\_\_ is used.

- Grid converter
- Grid splitter**
- Grid divider
- Grid compiler



**23)** \_\_\_\_\_ and \_\_\_\_\_ are the two important properties of Binding object.

Start, Destination

Items, Selected

**Source, Path**

BindTo, BindFrom

**24)** In multi touch events, a/an \_\_\_\_\_ id is assigned to each individual event.

Device

**Event**

CPU

Processor

**25)** Which of the following operation cannot be performed by using a View?

Filtering

Sorting

Grouping

**Searching**

**26)** Page also contains a few of its own properties that control the behavior of the \_\_\_\_\_.

container

**parent container** (Page#128)

child container

none of the given

**27)** Using \_\_\_\_\_ requires more overhead than \_\_\_\_\_ because of the extra tracking.

StaticResource, DynamicResource  
PermanentResource, TemporaryResource  
TemporaryResource, PermanentResource  
**DynamicResource, StaticResource**

**28)** Which function is used to create cancel button event of dialog box \_\_\_\_\_.

OnClickCancel()  
OnInitCancel()  
**OnCancel()**  
CancelClick()

**29)** Which of the following response show file not found error?

**404**  
500  
200  
304

**30)** \_\_\_\_\_ are high order functions that compose, combine, or otherwise modify functions in useful and interesting ways.

Modifiers  
Separators  
**Combinators**  
None of the given

**31)** Hyperlink element is used to link to \_\_\_\_\_.

html

**xaml** (Page#129)

http

website

**32)** “JavaScript” is \_\_\_\_\_ scripting Language.

Server

**Client**

Interpreter

Browser

**33)** The Java programming language has a specific class for creating splash screens, called \_\_\_\_\_.

Java.awt.start

Java.lang.splash

Java.start.screen

**Java.awt.SplashScreen**

**34)** To remove data binding between the source and the target, we can use \_\_\_\_\_ function.

StopBinding

RemoveBinding

**ClearBinding**

ResetBinding

**35)** You get Integrated Navigation in \_\_\_\_\_.

XAML

SDK

**XBAP** (Page#132)

HTML

**36)** In multi touch events, when multiple fingers are touching simultaneously, these events get raised for each finger \_\_\_\_\_.

Completely

Partially

**Independently**

Dependently

**37)** The \_\_\_\_\_ user interfaces, enabled by WPF, is getting a lot of attention.

Loutish

**Polished**

Coarse

Distracted

**38)** When your C# program is compiled, it creates a file called a/an\_\_\_\_\_, which is normally an executable or DLL library.

BIOS

C++

**Assembly**

Text

**39)** \_\_\_\_\_ where multiple GUI elements and many sources of events exist.

Control Language Interface

Content property

Event properties

**Visual programming**

**40)** In Visual Studio 2012, expression blend is \_\_\_\_\_ WPF feature.

80%

70%

**100%**

90%

**41)** To define a binary resource, add a \_\_\_\_\_ and set the build action resource or content (loose file).

folder

**file** (Page#133)

icon

page

**42)** A (n) \_\_\_\_\_ is a component of the structure of an event.

Event Architecture

Event Request

**Event Attribute**

Event Response

43) A \_\_\_\_\_ block has access to an "Exception" object that contains information about the error.

- Try
- Catch
- Throw**
- Finally

44) One of the ways to create an instance of a class is \_\_\_\_\_.

- Sequential heap
- System array**
- Factory method
- XAML compiler

45) There is/are \_\_\_\_\_ type/s of parameter/s for attributes.

- Four
- Three**
- One
- Two

46) A (n) \_\_\_\_\_ is a set of associated events.

- Event Consumer
- Event Producer
- Event Channel
- Event Stream**

47) If we require to set components in table (column and row) format, then which panel will be used?

StackPanel

DockPanel

**Gridpage**

TabPanel

48) \_\_\_\_\_ Method is used to move the file from one directory to another.

Import

**Move**

Export

None of given options

49) Not implementing some methods of the interface in the class is \_\_\_\_\_.

A warning

An exception

**An error**

Acceptable

50) Logical resources are introduced by wpf. Arbitrary .net object stored and named in an elements Resources prop. Typically meant to be shared by multiple \_\_\_\_\_ objects.

parent

child

**event** (Page#135)

function

**51)** A (n) \_\_\_\_\_ is a subscription mechanism for events.

- Raw Event
- Event Stream
- Event Channel**
- Event Producer

**52)** "Situation" is an event occurrence that requires a (n) \_\_\_\_\_.

- Class
- Object
- Reaction**
- Action

**53)** XML is a stricter version of \_\_\_\_\_.

- CSS
- C#
- Java
- HTML**

**54)** \_\_\_\_\_ contacts the service provider or the server.

- Event-driven
- Service Requester**
- Both of the above
- None of the given options



**55)** Any class, including the same class that the event is declared in, may register one of its methods with the \_\_\_\_\_.

**Event**

Delegate

Function

Class

**56)** \_\_\_\_\_ data source is provided by a Data Context.

Explicit

**Implicit** (Page#142)

Value

Context

**57)** \_\_\_\_\_ decouple producers and consumers.

Requests

**Events**

Functions

All of these

**58)** To declare an anonymous method, you just use keyword “\_\_\_\_\_”.

handler

event

**delegate**

none of the given

**59)** The common type system of C# has \_\_\_\_\_ types and \_\_\_\_\_ types.

Reference, Value

**Value, Reference**

Function, Data

Data, Function

**60)** There are \_\_\_\_\_ methods to read XML document.

**Two**

Three

Four

Five

**61)** Collectionviewsource has its own sortdescriptions and groupdescriptions properties and a Filter event to be used from \_\_\_\_\_.

event

container

**xaml (Page#150)**

xml

**62)** \_\_\_\_\_ can leave your program in an inconsistent state by not releasing resources or doing some other type of cleanup.

Functions

**Exception**

Abstraction

All of these

**63)** \_\_\_\_\_ are called by garbage collector.

Constructors

**Destructors**

Both of above

None of the given

**64)** Attributes are generally applied \_\_\_\_\_ in front of type and type member declarations.

Logically

**Physically**

Both of above

None of given

**65)** Multiple \_\_\_\_\_ are conventionally stored in multiple files.

**Classes**

Values

Variables

Functions

**66)** The \_\_\_\_\_, \_\_\_\_\_ and \_\_\_\_\_ of applications that use events, either directly or indirectly is called event-based programming.

Model, Code, Operation

Analyze, Design, Operation

**Design, Coding, Operation**

Code, Operation, Maintain

**67)** C# is a \_\_\_\_\_ and .NET is a \_\_\_\_\_.

Platform, Language  
**Language, platform**  
Package, Language  
Language, Package

**68)** Windows Presentation Foundations (WPF) was publicly announced in \_\_\_\_\_.

2000  
2001  
2002  
**2003**

**69)** WPF stands for:

Windows Powerful Foundations  
Windows Presentation Formations  
Windows Presentation Functions  
**Windows Presentation Foundations**

**70)** \_\_\_\_\_ declaratively instantiate the source object with a parameterized constructor.

data object  
**.net object** (Page#152)  
binding object  
files object

**71)** Value-types hold their value in \_\_\_\_\_ where they are declared.

- Variable
- Memory**
- Object
- Reference

**72)** Indexers can take any number of \_\_\_\_\_.

- Arrays
- Variables
- Parameters**
- All of these

**73)** Attributes add \_\_\_\_\_ to year program.

- Clearance
- Errors
- Meta Data**
- Ambiguity

**74)** Cast back to base type to call a/an \_\_\_\_\_ method of base.

- Instance
- Base Class
- Overridden**
- Derived Class

**75)** \_\_\_\_\_ is said to be stateless if the way it processes one event does not influence the way it processes any subsequent events.

- Event Producer
- Raw Event
- Event Processing**
- Event Stream

**76)** \_\_\_\_\_ is built from request-response and it moves away from monolithic applications.

- Event-driven architecture (EDA)
- Service-oriented architecture (SOA)**
- Both of above
- None of the given option

**77)** Object variables are references to the \_\_\_\_\_ object not the object themselves.

- Original**
- Alternative
- Primary
- None of the given

**78)** An indexer enables your class to be treated like a/an \_\_\_\_\_.

- Class
- Function
- Array**
- Pointer

79) Polymorphism needs the signatures to be the \_\_\_\_\_.

Different

**Same**

Alternative

None of the given

80) In the Binding Mode, the source is \_\_\_\_\_ whenever the target changes.

remain same

**updated (Page#153)**

revised

expired

81) Types of class members in C# are \_\_\_\_\_ and \_\_\_\_\_.

ostatic, instance

**oinstance, static**

opublic, private

ostatic, private

82) Events may live \_\_\_\_\_ events like in event logs.

Inside

**Outside**

Both of above

None of the given

**83)** In event-driven architecture (EDA), \_\_\_\_\_ sends event to \_\_\_\_\_.

Event Consumer, Event Producer

**Event Producer, Event Consumer**

Event Handler, Event Producer

Event Generator, Event Producer

**84)** Additional XML namespaces (on the root or on children) must be \_\_\_\_\_ to be used on any identifiers from that namespace.

Given a common prefix

Qualified with “Pre” keyword

**Given a distinct prefix**

Qualified with “Ext” keyword

**85)** Thread pool creates or reduces \_\_\_\_\_ threads using a hill climbing algo to maximize cpu usage and reduce slicing.

render

**real (Page#160)**

STA thread

none of the given

**86)** The interface forces each component to expose specific \_\_\_\_\_ members that will be used in a certain way.

**Public**

Private

Both of above

None of the given



**87)** \_\_\_\_\_ allows to keep the user interface description and implementation separate.

GDI

**WPF**

Avalon

Altia

**88)** Dependency properties are represented by \_\_\_\_\_.

**System.Windows.DependencyProperty**

System.Windows.Dependency.Property

System.Windows.Dependency

System.Windows.Property.Dependency

**89)** Suppose we want to restrict the user to don't decrease the height of a WPF element from a specific amount then which property will be used?

HeightMinimum

MinimumHeight

**MinHeight**

None of the given

**90)** \_\_\_\_\_ indirectly uses task completion source to implement methods returning Tasks.

Debugger

Linker

**Compiler (Page#169)**

Loader

**91)** If we want to scale an object in the 2-D x-y coordinate system then which transform class will be used?

Rotate Transform

Matrix Transform

**Translate Transform**

Skew Transform

**92)** Which of the following is/are not derived from “Control” class?

ListBox

StatusBar

Button

**None of the given**

**93)** Wait for a single event is \_\_\_\_\_ operation.

Waiting

Waste

**Blocking**

Idle

**94)** \_\_\_\_\_ method reads the whole document in memory.

XPath

**XmlDocument**

XmlReader

XmlLine

**95)** Which of the following events may or may not relate to an actual occurrence?

**Probabilistic Events**

Actual Events

Real Events

Expected Events

**96)** The System.Console is a \_\_\_\_\_ which enables us to do Console Input and Output.

Structure

**Class**

Namespace

Library

**97)** Clean room design is useful as a defense against \_\_\_\_\_.

Copyright

Trade secret infringement

**Copyright and trade secret infringement**

None of the given options

**98)** Clean room design is also called \_\_\_\_\_.

Clear Room Design

Wall Technique Design

**Chinese Wall Technique**

French Wall Technique

**99)** Which of the following is an occurrence within a particular system or domain?

Object

**Event**

Result

Message

**100)** TAP abbreviated as:

Task-based Async Plan

**Task-based Async Pattern** (Page#173)

Task-based Async Program

Task-based Async Preview

**101)** During the program execution, program can be stopped with the help of \_\_\_\_\_.

Attributes

Compiler

**Breakpoints**

Exception Handling

**102)** Which of the following does NOT include in event processing operations?

Deleting Events

Reading Events

**Terminating Events**

Transforming Events

**103)** The result of Exception can bring \_\_\_\_\_ in the program.

- Reliability
- Stability
- Inconsistency**
- Consistency

**104)** Graphical user interfaces and the event-driven model is not applied on which of the following?

- Web Application
- Console Application**
- Mobile Application
- Desktop Application

**105)** Events are based on the principle of \_\_\_\_\_.

- Request
- Response
- Coupling
- Decoupling**

**106)** \_\_\_\_\_ methods do not have names.

- Attribute
- Non-Anonymous
- Anonymous**
- None of given

**107)** Which of the following is an entity that introduces event into the system?

- Event Channel
- Event Producer**
- Event Stream
- Event Consumer

**108)** Anonymous methods \_\_\_\_\_ the code size.

- Double
- Expand
- Reduce**
- Extend

**109)** \_\_\_\_\_ events may or may not relate to an actual occurrence

- Layer
- Properties
- Event properties
- Probabilistic**

**110)** Task Parallel \_\_\_\_\_ exploit multicore for real parallel tasks.

- Structure
- Library** (Page#175)
- Class
- Namespace

**111)** The Main method returns a non-zero value which indicates the\_\_\_\_\_.

Source of Program

**Error in Program**

Termination of Program

Exception in Program

**112)** WPF4 was released in \_\_\_\_\_.

2012

**2010**

2005

2003

**113)** Extension methods can only be defined in \_\_\_\_\_ class.

**Static class**

Dynamic class

Normal class

String class

**114)** AML is compressed representation of \_\_\_\_\_.

CAML:NS

**XAML**

XAML:NS

CAML

**115)** Question # 56: \_\_\_\_\_ processing operations include reading, creating, transforming, and deleting events.

Observed Events

**Common event**

Deducted Events

Probabilistic Events

**116)** Static ctor exists to initialize class static members and called only \_\_\_\_\_.

**Once**

Twice

Anytime

All of the given

**117)** The \_\_\_\_\_ in the namespace indicate a hierarchy of nested namespaces.

Arrows

**Dots**

Semicolon

Brackets

**118)** \_\_\_\_\_ Interact with web page layout.

Java script

**HTML**

XML

DOM



**119)** Which of the following response show internal server error?

404

**500**

200

304

**120)** \_\_\_\_\_ is a formatting language.

HTML

**CSS** (Page#180)

Java

C#

**121)** Which of the following class supports data parallelism in "Task Parallel Library"?

System.Threading.Tasks

System.Task.Parallel

System.Task.Threading.Parallel

**System.threading.Task.Parallel**

**122)** What is the purpose of the following "jQuery" code? `$(, #navbar a')`

Find all the element whose name is navbar and then find a descendent a

**Find all the element whose ID is navbar and then find a descendent a**

Find all the element whose name is navbar and then find a ancestor a

Find all the element whose ID is navbar and then find a ancestor a

**123)** What message is used to send to destroy the object?

stop

**delete**

free

release

**124)** While dealing with "threads" in ".Net", one can avoid performance bottlenecks and enhance the overall responsiveness of his / her application by using \_\_\_\_\_ programming.

Multithreading programming

**Asynchronous programming**

Synchronous programming

Parallel programming

**125)** DOM is a \_\_\_\_\_ representation of data.

Tree

Graphical

**Object**

None of the given

**126)** "Callback" method is used to \_\_\_\_\_ the operation.

Invoke

Revoke

**Terminate**

Pause

**127)** Which of the following is not handled by the “Task Parallel Library (TPL)”?

- Partitioning of the work
- Scales the degree of concurrency
- Scheduling of threads
- Progress report handling**

**128)** Why we use “Alloc” message?

- To create a class
- To create an instance**
- To extend functions
- To inherent methods

**129)** Which of the following server(s) support “AJAX”?

- WWW
- SMTP
- HTTP**
- Both SMTP and HTTP

**130)** Which of the following is not a part of "cancellation" task?

- The calling thread does forcibly end the task**
- Notice and respond to the cancellation request in your user delegate
- Pass a cancellation token to your user delegate and optionally to the task instance
- Create and start a cancelable task

**131)** JQuery simplifies all steps except that of changing the webpage simplest is load function which loads \_\_\_\_\_ into an area of web page.

Function

Library

**HTML** (Page#193)

XAML

**132)** The "Task Based Asynchronous pattern" method returns either a "Task" or a "Task<TResult>", based on whether the corresponding \_\_\_\_\_ method returns "void" or a type "TResult".

Callback

**Synchronous**

Asynchronous

Return

**133)** "JavaScript" \_\_\_\_\_ is available in web browser.

Compiler

Linker

**Interpreter**

Conjunction

**134)** Which of the following is not true about task completion source?

**it is executable thing** (Page#175)

Provide Continuation facility

Support result return facility

Provide exception handling facility

**135)** A class that implements the „ICommand“ and supports „bubbling“ just like a routed event is known as \_\_\_\_\_.

- Executed command
- CanexecuteChange
- RoutedUICommand**
- Canexecute

**136)** To plug custom logic, you need to add a \_\_\_\_\_ to the element that will execute the command or any parent element.

- Execute command
- Helpcanexecute
- CommandBinding
- RoutedUICommand

**137)** In case of integrating Navigation to XBAP, "ShowNavigationUI" should be set to \_\_\_\_\_ in order to bypass integration.

- True
- Null
- False**
- 0

**138)** We use "GetDefaultView" method of \_\_\_\_\_ to get the default View.

- DataSource
- ViewDescription
- ViewCollection
- CollectionViewSource**

**139)** Which one of the following is used, if we want to add a window resource in procedural code?

Window.Resource.Add ();

**Window.Resoruces.Add();**

<Widows.Resources></Widows.Resources>

<Window.Resources></Window.Resources>

**140)** We can perform sorting through View by using an object of \_\_\_\_\_ class.

SortOrder

ViewDescription

**SortDescription**

ViewOrder

**141)** Question # 261: A \_\_\_\_\_ receives keyboard events only if it has keyboard focus.

Keyboard Controls

**UIElement**

Mouse

Keyboard

**142)** Frame has a \_\_\_\_\_ property used in enabling or disabling the bar.

NavigationUIBlock

ShowsNavigationUI

BlocknavigationUI

**NavigationUIVisibility**

**143)** A Window can spawn \_\_\_\_\_ number of additional Windows by instantiating a Window - derived Class and calling Show (...).

- Four
- Six
- Five
- Any**

**144)** \_\_\_\_\_ provides the logic behind the "Back" and "Forward" buttons.

- Hyperlink
- IFrame
- Journal**
- Navigation Window

**145)** A\An \_\_\_\_\_ allows the user to input text to label the current location on the map.

- mkMapView
- uiactivityindicatorview
- UITextField** (Page#213)
- mapmkview

**146)** In \_\_\_\_\_ browser app, you change "<TargetZone>Internet</TargetZone>" to "<TargetZone>Custom</TargetZone>"

- Partial - reject
- Full - trust**
- Partial - trust
- Full - reject

**147)** To check that the user either pressed left Alt key or right Alt key, the \_\_\_\_\_ is used.

IsDown

KeyStates.IsKeyDown

**IsKeyDown**

keyboardDevice.IsKeyDown

**148)** \_\_\_\_\_ supports the creation of applications that run directly in a web browser.

C#

**WPF**

HTML

C/C++

**149)** Which one of the following panels is most powerful, versatile and customizable?

Doc panel

Stack panel

**Grid Panel**

Canvas panel

**150)** Touch events are hallmark of \_\_\_\_\_.

computers

laptops

**mobile devices** (Page#216)

none of the given

---





**CS411 More MCQS**

**Final Term QUIZZES**

**Visual Programming**

**CS411 - Visual Programming**

Protocols are like \_\_\_\_\_ in other languages.

web pages

**interfaces**

structures

codes

**(Page#212)**

Data binding is about tying together arbitrary .NET \_\_\_\_\_.

Functions

Properties

**Objects**

Variables

An event that is raised whenever the value of "CanExecute" changes is known as \_\_\_\_\_.

Command

Execute

CanExecute

**CanExecuteChanged**

Multi touch events are categorized into \_\_\_\_\_ and \_\_\_\_\_.

Touch events, touchup events

Touchdown events, touchup events

**Basic touch events, higher-level manipulation events**

Advanced touch events, low-level manipulation events

In context of data binding, \_\_\_\_\_ contains the current item to get it synchronized with data Source.

String  
Template  
**List**  
View

Which of the following is an example of tunnel key event?

Key up  
Preview key entered  
**Preview key down**  
Key down

\_\_\_\_\_ has simple commands called tags.

JAVA  
CSS  
C#  
**HTML**      **(Page#179)**

Commonly we have two types of custom command bindings named as \_\_\_\_\_.

StartBindings and StopBindings  
**KeyBindings and MouseBindings**  
EventBindings and InstanceBindings  
ButtonBindings and TextboxBindings

Which of the following is not a string format property throughout WPF?

ItemStringFormat

StringFormat

ContentStringFormat

**RowHeaderStringFormat**

To design a complex Interface, which of the following technique is best to achieve the required results?

Panels composed in three panels

Panels composed in two panels

**Panels composed within panels**

Panels composed in single panel

\_\_\_\_\_ is used to perform navigation.

Session

**Hyperlink**

Internet protocol

Hypertext markup language code

The Java programming language has a specific class for creating splash screens, called \_\_\_\_\_.

Java.awt.start

Java.lang.splash

Java.start.screen

**Java.awt.SplashScreen**

We use "UIElement" property ClipToBounds= "false" when \_\_\_\_\_.

We want area child element don't cross the boundary of parent

**We want area of child element is allowed to cross the boundary of parent**

Parent area also increases on increasing of area of child element

None of given

In Parallelism true concurrency at \_\_\_\_\_ level operations.

upper

**bottom**

**(Page#171)**

high

lower

Consider the following C# code segment: `button.Background = (Brush) new BrushConverter().ConvertFrom ("SystemColors.WindowBrush");`  
Which one of the following is equivalent XAML code?

Button Background= "SystemColor.WindowsBrush"/>

Button Background= "SystemColor.WindowBrush"/>

**Button Background= "SystemColors.WindowsBrush"/>**

Button Background= "SystemColors.WindowBrush"/>

All elements of WPF have following property/properties.

Width

Height

**Height and Width**

None of given options

With the help of WPF, an ugly looking application can be \_\_\_\_\_ by the designers.

- Rearranged
- Re-created
- Rejected
- Re-themed**

Which of the following components generates an input Event?

- Printer
- Plotter
- Multi-Touch** (Page#114)
- Speaker

Graphical user interfaces and the event-driven model are not applied on which of the following?

- Web Applications
- Mobile applications
- Desktop Applications
- Console Applications**

C# is most often used with some implementation of the \_\_\_\_\_.

- Compact Language Interface
- Common Language Infrastructure**
- Control Language Infrastructure
- Control Language Interface

In C#, comments are written using \_\_\_\_\_.

# and /\* /\*

**// and /\* /\***

# and /\*

// and /\* /\*

Binding binds \_\_\_\_\_ properties together and keeps a communication channel open.

**two**

**(Page#140)**

three

four

five

Attributes are declared \_\_\_\_\_ the class/function.

Outside

After

**Within**

Above

XML document is readable by \_\_\_\_\_.

Human only

Machine only

No one

**Machine and Human both**

"Console" is a/an \_\_\_\_\_ class in the "System" namespace.

Input  
Dynamic  
**Static**  
Virtual

The only \_\_\_\_\_ .Net language has an intrinsic understanding of dependency Properties.

Vb.net  
**Xaml**  
C#  
J#

Which of the following grabs the "OK" button by only knowing its name?

Button okButton = (Button)window.GetName("okButton")  
Button okButton = (Button)window.getElementByName("okButton")  
**Button okButton = (Button)window.FindName("okButton")**  
Button okButton = (Button)window.GetButton("okButton")

Unlike type converters, however, markup extensions are invoked from XAML with \_\_\_\_\_.

Bridge assemblies  
**Explicit and consistent syntax**  
Wrapper code  
None of the given options



Which statement is True about interfaces?

An interface can contain only methods, variables, events, and indexers.

An interface can contain only variables, properties, events, and indexers.

An interface can contain only methods, properties, variables, and indexers.

**An interface can contain only methods, properties, events, indexers.**

Events can be \_\_\_\_\_.

Specialized

Composed

Generalized

**All of the given options**

g++ is a command of \_\_\_\_\_.

Dev C++

**Unix based system**

Windows based system

None of the given options

\_\_\_\_\_ reads entire document in memory.

**Xmldocuments**

Xmlreader

Both of above

None of the given

\_\_\_\_\_ may contain events.

- Requests
- Service
- Messages**
- Applications

A customer order can be represented as \_\_\_\_\_.

- Event
- Request
- Event or Request**
- All of the given

Markup extensions are invoked from \_\_\_\_\_ with explicit and consistent syntax.

- C#
- HTML
- XAML**
- None of the given

All the members of interfaces are implicitly \_\_\_\_\_.

- Private
- Static
- Public**
- Abstract

A compiled C# file is called \_\_\_\_\_.

- Compiled File
- Source File
- Assembly File**
- EXE File

\_\_\_\_\_ add declarative information to your programs.

- Attributes**
- Functions
- Exception
- Objects

Anonymous method is a method without a name.

- True**
- False

“out” parameters which are not used for return values or the “params” argument for variable arguments.

- True
- False**

\_\_\_\_\_ types have the notion of referential identity.

- Value
- Reference**
- Both of above
- None of the given

\_\_\_\_\_ let any classes behave like an array.

Properties

Fields

**Indexers**

Finalizers

\_\_\_\_\_ are algorithms that operate on data.

Variables

Functions

**Methods**

Classes

\_\_\_\_\_ is an event that is introduced into an event processing system by an event producer.

Event Producer

Event Consumer

**Raw Event**

Event Stream

Events and \_\_\_\_\_ work hand in hand.

Parameters

**Delegates**

Functions

Data Members

C# event is a class member that is \_\_\_\_\_ whenever the event it was designed for occurs (fires).

**Activated**

Deactivated  
Transformed  
Associated

\_\_\_\_\_ is a static class in the System namespace.

**Console**

Pointer  
Variable  
Function

Default value of first member is \_\_\_\_\_.

**0**

1  
2  
3

\_\_\_\_\_ are inherited by classes which provide the real implementation.

Functions  
Variables  
**Interfaces**  
Objects

\_\_\_\_\_ is basically array of arrays.

- Stack
- Pointer
- Jagged**
- Function

The initial name for C# was \_\_\_\_\_.

- COAL
- COOP
- COAP
- COOL**

BAML is compressed representation of \_\_\_\_\_.

- CAML:NS
- XAML**
- XAML:NS
- CAML

Extension methods \_\_\_\_\_ access the private data members of the class in which they are extended.

- May
- Cannot**
- May not
- Can

Which of the following is/are not derived from “Control” class?

- ListBox
- StatusBar
- Both of above
- None of the given**

\_\_\_\_\_ events may or may not relate to an actual occurrence.

- Observed Events
- Deducted Events
- Probabilistic Events**
- None of the above

\_\_\_\_\_ is an entity that receives events from the system.

- Event Producer
- Event Consumer**
- Event Channel
- Event Generator

The easiest way to declare an event is to put the event keyword in front of a \_\_\_\_\_ member.

- Interface
- Delegate**
- Class
- Struct

\_\_\_\_\_ can be used on non-data bound but inside the element it almost always make sense to use data binding.

Event

**Template**

**(Page#144)**

Data

Function

\_\_\_\_\_ is typing together arbitrary objects.

data frame

data store

**data binding**

**(Page#140)**

markup extension

-----Wish U Best of L|U|C|K for EXAMS -----

**MUHAMMAD FAISAL DAR**

**AL-BARQ CAMPUS (VGIWO1) GUJRANWALA**

Virtual University of Pakistan